

Rapidline Un-metered standpipes are engineered to perform exceptionally well in challenging environments. Made from high-quality aluminium with a gunmetal base, these standpipes are constructed to endure rigorous use and harsh conditions. Their lightweight yet strong construction ensures reliable performance while being easy on the operator.

Our standpipes are compatible with all standard spring hydrants throughout Australia.

CODE	DESCRIPTION	LENGTH	WEIGHT
UMSP25-BSP-S	BSP Outlet 25mm	940mm	7.2 Kg
UMSP65-MFB-S	MFB Outlet 65mm Short Version	940mm	7.4 Kg
UMSP65-MFB-L	MFB Outlet 65mm Long Version	1100mm	7.9 Kg
UMSP65-QRT-S	QRT Outlet 65mm Short Version	940mm	7.4 Kg
UMSP65-QRT-L	QRT Outlet 65mm Long Version	1100mm	7.9 Kg
UMSP65-CFA-S	CFA Outlet 65mm Short Version	940mm	7.4 Kg
UMSP65-CFA-L	CFA Outlet 65mm Long Version	1100mm	7.9 Kg

Measurements are taken from the bottom of the base to the top handle  $% \left\{ 1,2,\ldots ,n\right\}$ 

## **OPTIONAL EXTRA'S**

- Powder Coating is available for an additional cost.
- Laser marking with Serial Numbers or Branding is also available.
- Single Check Backflow Device for 65mm variants



## Proudly manufactured and tested in Australia

SPECIFICATIONS		
Maximum Working Pressure	2500 kPa	
Finish	Unpainted	
Body	Aluminium (65mm) Galvanised Steel (25mm)	
Base	Gun Metal	
Spindle	Stainless Steel	
Base Seal	EPDM	
Repairable	Yes	
Swivel Head	65mm Only	

## **IMPORTANT INFORMATION**

You may need to get approval from your local water authority to use a Standpipe. All authorities have different regulations and requirements. Please check with your local Authority prior to purchasing.

The warranty covers manufacturer defects for 12 months from the purchase date of the standpipe. Misuse, such as attaching bars to the hydrant for removal or hammering the spindle, will nullify the warranty. Refer to the sticker on the standpipe for the correct operating instructions.

